

3Ø, 600V distribution kiosk used to add an additional secondary service to a site. Designed to house the utility connection and a 30-circuit breaker panel. Full dead front covers and connections included for ease of installation.

RATINGS:

CSA CERTIFIED 3R ENCLOSURE

CERTIFIED FOR USE AS SERVICE ENTRY

FEATURES

- **Fully Welded CSA Construction**
- Built from Marine Grade Aluminum
- **Designed for Pad Mount Applications**
- Stainless Steel 3 Point Handle c/w Dual Padlock Provision
- Terminal Blocks for BC Hydro Connection
- 21 kA Rated Main Breaker
- Dead Front/Touch Safe Interior
- **Expansion Space for Additional Controls/Devices**
- Viewing Window and Meter Base

OPTIONS

- **Custom Size Enclosures**
- **Custom Colour Powder Coating**
- CSA 1, 3R, 3, 4 or 4X Ratings
- **Different Distribution Ratings**
- Convenience Receptacle
- Light
- Climate Control
- Insulation



CAT No:	MAIN BREAKER	PHASE	VOLTAGE FOR 21kA	SIZES
KDP3-A-100	100A	3	347/600V	60 x 36 x 22
KDPS-A-150	150A	3	347/600V	60 x 36x 22
KDP3-A-200	200A	3	347/600V	60 x 36 x 22

^{*}For custom options, speak with your sales representative.